

# P O T T E R Y B A R N

## Tic Tac Toe mounting instructions

### Note:

This mounting hardware is meant for dry wall/stud mounting only. If walls are concrete, brick or plaster, please consult your local hardware store for assistance. For safety and ease of mounting, installation is recommended using two people.

### Tools needed

Level, Tape Measure, Stud Finder, #2 Phillips screwdriver, Pencil


### Hardware Included:

(2) Stud Mount Screws

(2) Toggle Screws

(2) Toggle Anchors

(The Toggle Anchors and Toggle Screws are meant for dry wall only)



Stud Mount Screw

Toggle Screw

Toggle Anchor

### Mounting Instructions:

1. Determine your desired hanging location. Measure the distance between the d-rings on the back of the shelf, making sure the measurements are taken from the centers of both d-rings.
2. Record this measurement on the wall with a pencil. Use a carpenter's level and a tape measure to ensure a level installation.
3. Stud mounting is always best, so try to position the d-rings over studs if possible. Use a stud finder to locate a stud in desired location. If any of the d-rings align with stud, use provided metal mounting screws. If there is no stud, the wall anchors/metal screws are both required.

### Dry Wall Mounting

1. Use a Phillips screwdriver to insert the wall anchors. Do not "push" or drive the anchors into the wall, it is designed to bore into the wall like a drill bit. Slowly turn the anchors clockwise while applying pressure until the flange just touches the wall.
2. Insert the metal screw into the wall anchor turning clockwise leaving approximately ½" between the back of the screw head and the wall.
3. Align the d-rings over the screw heads and slide the shelf down until the tops of the d-rings rest on the screws. Tighten or loosen screws as needed to fit the shelf snugly against the wall.

### Stud Mounting

1. With a Phillips screwdriver (or drill) insert metal screws into the stud clockwise until tight.
2. Align the d-rings over screw heads and slide the shelf down until the tops of the d-rings rest on the screws.

thank you for your purchase