

P O T T E R Y B A R N

Capiz Flushmount

Important Safety Instructions:

- These instructions are provided for your safety. It is very important that they are read carefully and completely before beginning the installation of this lighting fixture.
- We strongly recommend that a professional electrician install all direct wire fixtures.
- **This fixture has been rated up to 60 Watt TYPE A standard incandescent light bulb (not Included) or use only UL listed Self-Ballasted CFL max. 13 watts (included for California Customers). To avoid the risk of fire, do not exceed the recommended wattage.**
- The lighting fixture is meant for indoor use, DRY LOCATIONS ONLY.
- **Save these instructions.**

WARNING:

- **To reduce the risk of fire, electrical shock or personal injury, always turn off light fixture and unplug, allowing it to cool prior to replacing light bulb.**
- **Do not touch bulb when fixture is turned on. Do not look directly at lit bulb.**
- **Keep flammable materials away from lit bulb.**
- **This lighting fixture contains lead, a chemical known to the State of California to cause cancer, birth defects and other reproductive harm. Wash hands after installing, handling, cleaning or otherwise touching this light fixture.**

Pre-assembly:

- Remove all parts and hardware from box along with any plastic protective packaging. Do not discard any contents until after assembly is complete to avoid accidentally discarding small parts or hardware.
- For your safety and convenience, assembly by two people is recommended

Parts Included:

- (1) Fixture (F)
- (2) socket on mounting plate (B)

Hardware Included:

- (3) Plastic wire connectors (A)
- (2) Screw (B)
- (2) Mounting screws (C)

Tools Required: (not included)

1. Electrical tape
2. Philips screwdriver
3. Wire Cutters
4. Pliers
5. Step Ladder
6. Drill and drill bit

Preparing the light fixture:

1. **SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER!**
2. Carefully unpack all fixture parts and hardware and lay out on a clear workspace.

Installation Instructions:

1. Separate light fixture (F) from Mounting Plate (B) first by turning counterclockwise.
2. Gently pull wiring from junction box and allow to hang.
3. Carefully inspect the flushmount's wires. The NEUTRAL FIXTURE WIRE is white. The HOT FIXTURE WIRE is black. The green-yellow wire is the GROUND WIRE.
4. Attach the GROUND WIRE from the fixture to the GROUND JUNCTION BOX WIRE from the outlet (usually green or bare wire). Fasten each together with a plastic wire connector (A) and wrap the connection with electrical tape. Be sure no wire strands are exposed. If your outlet box **DOES NOT** have a ground wire, wrap the fixture's bare ground wire. **IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.**
5. Connect the NEUTRAL FIXTURE WIRE to the NEUTRAL JUNCTION BOX WIRE (usually white), twisting wire ends clockwise. Fasten each together with a plastic wire connector (A) and wrap the connection with electrical tape. Be sure no wire strands are exposed. Connect the HOT FIXTURE WIRE to the HOT JUNCTION BOX WIRE (usually black), twisting wire ends clockwise. Fasten each together with a plastic wire connector (A) and wrap the connection with electrical tape. Be sure no wire strands are exposed. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.**
6. Gently tuck the wire connections neatly into the wall junction box.
7. Secure the mounting plate(B) with screw (C) and screws (D) by Phillips screwdriver.
8. Insert 2 60-watt Type A bulb (not included) to the socket
9. Insert the light fixture (F) to the mounting plate (B).
10. Assembly is finished.
- 11.** Restore power to junction box and test fixture.

Care instructions:

- Always turn off power to fixture. Wipe clean with a soft, dry cloth or static duster.
- Always avoid the use of harsh chemicals or abrasive cleaners as they may cause damage to the fixture's finish.

